



## Renewable Energy Technology -For Better Tomorrow

**Ramchandra.T.Jadhav**

Department of General science (physics) ,LNBC Institute of Engg and Tech

RAIGAON SATARA (Maharashtra)

Mobile- 9423829482, 9421126589

Email- [ramchandrajadhav.1470@rediffmail.com](mailto:ramchandrajadhav.1470@rediffmail.com), [Jadhav.drramchandra434@gmail.com](mailto:Jadhav.drramchandra434@gmail.com)

### INTRODUCTION

Energy is an essential pre- requisite for the economic and social development of the country. Energy and environment are the two basic components of the new global of sustainable development. Development involves improving the material condition and the total quality of the vast majority of the human race living in developing countries.

Since the dawn of civilization, man has been dependent on energy in one form or the other. The story of the energy starts with wood, wood came to be replaced by coal and coal by oil only partially. Now a stage appears to have been reached when oil may also have to be substituted by Biomass.

Sugar industry is one of the most important industries, playing vital role in the economic development of the nation and also a most advanced processing industry in the agricultural sector in India. In our country more than 377 sugar mills, in which 0.25 million tones of sugar cane is crushed per day, 4% of cane crushed is press mud. After processing for cane sugar, the precipitate otherwise down at the bottom of the clarifier is called press mud, otherwise known as sugar cane mud, sugar cane filter mud, filter press cake, and filter mud. Mostly the cane leaves are supposed to be nuisance to the farmers and are so called waste residues. The bagasse and cane leaves are good candidates for gasification.

### MATERIALS AND METHODS

At the time of harvesting sugarcane crop, the top of the cane are removed and the stems are cleaned of their leaves (trash), on the average the cane tops and trash constitute 25-30% of the cane weight in the field.

#### FIELD SURVEY

field survey was conducted to estimate the quantitative availability of cane leaves except cane tops. Five plots of one acre area of sugarcane cultivated fields were selected and marked. The total cane rows planted in each plot per acre were counted. The counts were made for number of cane plants per row and total leaves per plant. The leaves from randomly selected plants were collected and carried to the laboratory for the measurement of its weights and its proximate analysis. All samples were selected by Random sampling method.

**Analytical methods**-are moisture, total solids, volatile solids and fixed solids.

For moisture-randomly selected samples of feed stock was weighted and then heated at 80°C in oven for evaporating the moisture.

For total solids- the determination of quantity of solids is essential to observe the gasification efficiency. The weight of sample after the evaporation of the moisture was calculated as total solids.

Volatile solids- the weighted total solids were ignited in the muffle furnace at a temperature of 550°C+50°C for two hours. Difference between total solids and the weight of sample after ignition.

Fixed solids- biologically inert material is referred as fixed solids. The weight of sample residue after the ignition of dry matter at 550°C+50°C in muffle furnace was calculated as fixed solids.

### FEED STOCK COLLECTION AND PREPARATION

Cane leaves were dried in muffle furnace 80°C for 48 hours to remove its moisture content. Electrical grinder (Nippon Ele. India) .Grinder used for the preparation of powder samples. The samples of

four different particulate sizes were prepared and sieved through the respective sieves. The grain size employed in the present investigation was in

### PROCESS PRINCIPLE

Experimental set up is as shown in fig 4. This is schematic sketch. The various reactions that take place during the gasification process can be synthesized to elementary steps to have a clear understanding about the entire process. Gasification process is carried out in four distinct stages 1. Oxidation 2. Drying 3. Pyrolysis 4. Reduction.

Oxidation process -required temperature 900-1200°C. The products of oxidation zone are high temperature gases containing products and water vapors. In drying- the drying process usually air dried biomass contains moisture in the range 13-15%. It occurs below 110°C. Due to this, weight of a material is reduced. In pyrolysis- this zone in which biomass loses all its volatiles and get converted into two parts as 1. Primary pyrolysis zone- in 200-600°C range. And 2. secondary zone-300-600°C range. Reduction- this zone is maintained within close temperature limits 900°C to 600°C. The final result is a gas consisting mainly CO, H<sub>2</sub>, N<sub>2</sub>, CO<sub>2</sub> steam and hydrocarbons.

### TABULAR GASIFIRE-A NEW CONCEPT

The availability of low density feed stock is considerable in India, especially the waste generated in agro- industries and farms. This includes the bagasse, cane trash, rice husk etc. to overcome the difficulties in utilization of these wastes for energy generation through the thermal decomposition, the new concept of tubular gasfire is taking roots recently.

### RESULTS AND DISCUSSION

The tubular powdery gasfire was tested for its use to gasify the powdery biomass under the laboratory conditions. Gasification process was not observed for bagasse below 800°C, but little gasification was observed for cane leaves at the temperature above 600°C. The percentage of gasification for cane leaves was increased from 600°C to 1000°C. And attained the maximum possible percentage of gasification for lower powdery grain size. The overall percentage gasification for cane leaves was higher at smaller grain size of powder and was decreased at larger grain size. For the small grain size there was the grain attachments to the surface. And formation of a layer was observed. But for higher grain size was less gasified. To have more gasification without layer formation of burned powder, the grain sizes of 1mm to 2.5mm are likely to be useful under continuous operations of gasification with least nuisance of layer formation and optimum percentage gasification.

### CONCLUSIONS

The tubular powdery gasifier model is efficient for gasification of the powders of grain size up to 2.5mm. The laboratory results are encouraging for the fabrication of pilot scale multitubular powdery gasifier to utilize the loose bagasse and cane leave.

### REFERENCES

1. Rai.G.D(1986), Non conventional Energy sources Khanna Publishers, Delhi.
2. A.Bridgwater and K. Lidgren (1981) Household waste Management in Europe-Economics and Technique.
3. Vimol.O.P and Bhatt .M.S (1989) wood Energy system, K.L.Publication, New Delhi.
4. Singh.S.N.and J.P .Mittal (1995), proceeding of National conference on conversion and utilization of Biomass, held at M.G.I.Bakoli, New Delhi.
5. Prof.A.R.Lakshmanan.G.Kuppuswamy and A.Jeyabal Annamalai University.Biogas Generation from sugarcane filter cake laboratory and pilot plant study.
6. Ram Chandra, Santosh Rana and S.P.Singh. Centre of Energy studies and Research Devi Ahilya Vishwavidyalaya, Khandwa Road. Indore. Efficient use of Biomass for Rural Development.